



HellermannTyton

SPIRALSLANGE

Konverteringstabell

Gammel type					Ny type					
Navn	Farge	El.nr	Lengde	Diameter mm	Navn	Farge	El.nr	Lengde	Diameter mm	Bunte Ø mm min - max

Materiale : Polyethylen

1NFP	Naturell	13 452 12	30m	1,6	SBPE1.5	Naturell	13 451 81	30m	1,5	1,6 - 8,0
1NFP	Sort	13 451 40	30m	1,6	SBPE1.5	Sort	13 451 82	30m	1,5	1,6 - 8,0
2NFP	Naturell	13 452 13	30m	4,1	SBPE4	Naturell	13 451 83	30m	4,0	5,0 - 20,0
2NFP	Sort	13 451 41	30m	4,1	SBPE4	Sort	13 451 84	30m	4,0	5,0 - 20,0
3NFP	Naturell	13 452 14	30m	9,6	SBPE9	Naturell	13 451 85	30m	9,0	10,0 - 100,0
3NFP	Sort	13 451 42	30m	9,6	SBPE9	Sort	13 451 86	30m	9,0	10,0 - 100,0
4NFP	Naturell	13 452 15	30m	13,7	SBPE16	Naturell	13 451 87	30m	16,0	20,0 - 150,0
4NFP	Sort	13 451 43	30m	13,7	SBPE16	Sort	13 451 88	30m	16,0	20,0 - 150,0

Materiale : Polyethylen flammehemmende

1FRP	Hvit	13 452 09	30m	1,7	SBPEFR1.5	Hvit	13 451 89	30m	1,5	1,6 - 8,0
1FRP	Sort	-	30m	1,7	SBPEFR1.5	Sort	13 451 90	30m	1,5	1,6 - 8,0
2FRP	Hvit	13 452 10	30m	4,4	SBPEFR4	Hvit	13 451 91	30m	4,0	5,0 - 20,0
2FRP	Sort	-	30m	4,4	SBPEFR4	Sort	13 451 92	30m	4,0	5,0 - 20,0
3FRP	Hvit	13 452 11	30m	10,2	SBPEFR9	Hvit	13 451 93	30m	9,0	10,0 - 20,0
3FRP	Sort	-	30m	10,2	SBPEFR9	Sort	13 451 94	30m	9,0	10,0 - 20,0